

Pendiro EC 125

Article number: 81030087

LIGHT TECHNOLOGY

| | |
|----------------------|---------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 3270 lm |
| System power | 34 W |
| Luminaire Efficiency | 96 lm/W |
| Reflector | Flood |
| Beam angle | 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | black |

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.73 | 6492.9 |
| 2.0 m | 1.46 | 1623.2 |
| 3.0 m | 2.19 | 721.4 |
| 4.0 m | 2.92 | 405.8 |
| 5.0 m | 3.65 | 259.7 |
| Ø (m) | | E0(0°) [lx] |

