

## Intara CX

Article number: 51410001

### LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | LED       |
| Light colour         | 830       |
| Luminous flux        | 3060 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 90 lm/W   |
| Reflector            | Downlight |
| Beam angle           | 60°       |
| Controller           | On/Off    |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 0.67 kg     |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | black       |

### OPTIONEEL

Front ring with RAL / NCS, emergency light function for central supply, fire protection cover (up to 34 W), ceiling reinforcing profile for modular ceiling, reduction ring




Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with homogeneous light distribution pattern, diffuser lens, translucent, darklight reflector, aluminium, metallised, highgloss, luminaire head die-cast aluminium, powder-coated, ; mounting ring die-cast aluminum, front ring and coverblind plastic, black, separate driver unit

76500076 driver unit, On/Off, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500123 driver unit, Casambi, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 23 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 1.28 | 2884.1      |
| 2.0 m | 2.56 | 721.0       |
| 3.0 m | 3.84 | 320.5       |
| 4.0 m | 5.12 | 180.3       |
| 5.0 m | 6.40 | 115.4       |
| Ø (m) |      | E0(0°) [lx] |

