

Intara RD 165

Article number: 51090007

LIGHT TECHNOLOGY


LED	COB
Light colour	835
Luminous flux	5520 lm
System power	47 W
Luminaire Efficiency	117 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

LUMINAIRE

Swivel angle	+/- 25°
Weight	0.9 kg
Protection rating . class	IP 20 . III
Luminaire colour	silver

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, silver, separate driver unit

76500092 driver unit, On/Off, 220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500093 driver unit, DALI, 220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

