

## Intara XR

Article number: 50870040

## LIGHT TECHNOLOGY



|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 2340 lm    |
| System power         | 23 W       |
| Luminaire Efficiency | 102 lm/W   |
| Reflector            | Spot       |
| Beam angle           | 20°        |
| Controller           | On/Off     |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Swivel angle              | +/- 25°    |
| Weight                    | 0.69 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | white      |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, white,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

