

Intara TX

Article number: 50850006

LIGHT TECHNOLOGY

LED	SMD
Light colour	840
Luminous flux	11050 lm
System power	72 W
Luminaire Efficiency	153 lm/W
Reflector	Xtra WideFlood
Beam angle	90°
Controller	On/Off

LUMINAIRE

Weight	3.2 kg
Protection rating . class	IP 20 . I
Luminaire colour	white



Lay in luminaire with LED, rated life of the LED L90/B50 50000 h (ambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6250 lm), 42 W (6960 lm), 47 W (7670 lm), 52 W (8360 lm), 57 W (9050 lm), 62 W (9730 lm), 67 W (10390 lm), 72 W (11050 lm), 57 W preselected, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 21 luminaires per circuit (B16A fuse)

Order accessories separately!

Fastening set for Ceiling Systems with visible supporting profile:

5080Z600 for Ceiling Systems 600, white

5080Z625 for Ceiling Systems 625, white

Cover bracket für Ceiling systems:

5080C600 for Ceiling Systems 600, white


5080C625 for Ceiling Systems 625, white

Through-Wiring:

765Y4000 DALI T-Connector 5-pole and cable with plug/socket -5 pole, GST 18/5 (DALI), L= 4000 mm

inclusiv driver unit: 220-240 V~ / 50-60 Hz, DALI, max. 15 luminaires per circuit (B16A fuse), temperature protection, temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	2.0 1.9	3826
2.0 m	4.0 3.9	957
3.0 m	6.0 5.8	425
4.0 m	8.0 7.8	238
5.0 m	10.0 9.7	153
	Ø (m)	E0(0°) [lx]

