

Ontero TX

Article number: 21380005

LIGHT TECHNOLOGY

| | |
|----------------------|-----------|
| LED | SMD |
| Light colour | 835 |
| Luminous flux | 10630 lm |
| System power | 72 W |
| Luminaire Efficiency | 148 lm/W |
| Reflector | WideFlood |
| Beam angle | 60° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Rotation angle | 330° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern (60°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6010 lm), 42 W (6700 lm), 47 W (7380 lm), 52 W (8050 lm), 57 W (8710 lm), 62 W (9360 lm), 67 W (10000 lm), 72 W (10630 lm), 57 Watt preselected, rotation angle 330°, On/Off, DIP-Switch, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 16 luminaires per circuit (B16A fuse)

inclusive driver Unit: 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

