

## Ontero TX

Article number: 21620008

### LIGHT TECHNOLOGY

LED	SMD
Light colour	835
Luminous flux	10980 lm
System power	72 W
Luminaire Efficiency	153 lm/W
Reflector	Doppelt Asymmetrisch Medium
Beam angle	2 x 25°
Controller	On/Off

### LUMINAIRE

Rotation angle	330°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	white



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6210 lm), 42 W (6920 lm), 47 W (7620 lm), 52 W (8310 lm), 57 W (8990 lm), 62W (9660 lm), 67 W (10330 lm), 72 W (10980 lm), 57 Watt preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, white, Multiadapter

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

