

Pendiro TX


Article number: 80870005

LIGHT TECHNOLOGY

LED	SMD
Light colour	835
Luminous flux	5530 lm
System power	38 W
Luminaire Efficiency	146 lm/W
Reflector	Doppelt Asymmetrisch Medium
Beam angle	2 x 25°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Weight	1.2 kg
Protection rating . class	IP 20 . III
Luminaire colour	matt silver



Suspended luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, luminaire housing sheet steel, powder-coated, matt silver, power supply via suspension cables

Canopy, sheet steel, powder-coated, inkl. SELV-, canopy /supply set (E-set) please order separately

76500129 E-Set for 3-Ph Track, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), silver matt

76500130 E-Set with Canopy, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), silver matt

76500135 E-Set for 3-Ph Track, Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), silver matt

76500136 E-Set with Canopy Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), silver matt

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

