

# Pendiro TX


Article number: 80870013

## LIGHT TECHNOLOGY

|                      |                           |
|----------------------|---------------------------|
| LED                  | SMD                       |
| Light colour         | 830                       |
| Luminous flux        | 5360 lm                   |
| System power         | 38 W                      |
| Luminaire Efficiency | 141 lm/W                  |
| Reflector            | Doppelt Asymmetrisch Wide |
| Beam angle           | 2 x 25°                   |
| Controller           | On/Off                    |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 330°        |
| Weight                    | 1.2 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | matt silver |



Suspended luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with slight horizontal brightening, Combination of asymmetrical PMMA lenses and 60 ° TIR lenses made of PMMA, luminaire housing sheet steel, powder-coated, matt silver, power supply via suspension cables

Canopy, sheet steel, powder-coated, inkl. SELV-, canopy /supply set (E-set) please order separately

76500129 E-Set for 3-Ph Track, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), silver matt

76500130 E-Set with Canopy, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), silver matt

76500135 E-Set for 3-Ph Track, Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), silver matt

76500136 E-Set with Canopy Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), silver matt

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

