

Pendiro TX

Article number: 80880009

LIGHT TECHNOLOGY

LED	SMD
Light colour	840
Luminous flux	9810 lm
System power	64 W
Luminaire Efficiency	153 lm/W
Reflector	Doppelt Asymmetrisch Medium
Beam angle	2 x 25°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Weight	3.7 kg
Protection rating . class	IP 20 . III
Luminaire colour	matt white



Suspended luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (6250 lm), 42 W (6780 lm), 45 W (7290 lm), 49 W (7810 lm), 53 W (8310 lm), 56W (8810 lm), 60 W (9310 lm), 64 W (9810 lm), 53 W preselected, luminaire housing sheet steel, powder-coated, matt white, power supply via suspension cables.


Canopy, sheet steel, powder-coated, including SELV driver with adjustable system performance via DIP switch, temperature protection, canopy /supply set (E-set) please order separately:

76500084 E-Set for 3-Ph Track, DALI, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), white matt

76500085 E-Set with Canopy, DALI, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), white matt

76500080 E-Set für 3-PH-Stromschiene, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), white matt

76500081 E-Set with Canopy, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), white matt



Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.