

Ontero EC 125

Article number: 21110046

LIGHT TECHNOLOGY

LED	COB
Light colour	830
Luminous flux	4230 lm
System power	34 W
Luminaire Efficiency	124 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

LUMINAIRE

Rotation angle	350°
Swivel angle	210°
Weight	2.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	white

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, white, rotation angle 350°, swivel angle 210°, Multiadapter, DALI, 220-240 V, 50/60 Hz, max. 24 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	25546.6
2.0 m	0.62	6386.7
3.0 m	0.93	2838.5
4.0 m	1.24	1596.7
5.0 m	1.55	1021.9
Ø (m)		E0(0°) [lx]

