

# Ontero EC 125

Article number: 21080111

## LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | Meat&Fish |
| Luminous flux        | 2670 lm   |
| System power         | 41 W      |
| Luminaire Efficiency | 65 lm/W   |
| Reflector            | Spot      |
| Beam angle           | 20°       |
| Controller           | On/Off    |

## LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 350°      |
| Swivel angle              | 210°      |
| Weight                    | 2.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |

## OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, white, rotation angle 350°, swivel angle 210°, Multiadapter, On/Off, 220-240 V, 50/60 Hz, max. 24 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.36 | 13728.1     |
| 2.0 m | 0.72 | 3432.0      |
| 3.0 m | 1.08 | 1525.3      |
| 4.0 m | 1.44 | 858.0       |
| 5.0 m | 1.80 | 549.1       |
| Ø (m) |      | E0(0°) [lx] |

