

Ontero IC



Article number: 21500003

LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	2140 lm
System power	17 W
Luminaire Efficiency	126 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off


LUMINAIRE

Rotation angle	330°
Swivel angle	+/- 90°
Weight	1.1 kg
Protection rating . class	IP 20 . II
Luminaire colour	black



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 330°, swivel angle +/- 90°, In-Track-Adapter, Casambi, 220-240 V~ / 50-60 Hz, temperature protection, max. 64 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.34	13021.1
2.0 m	0.68	3255.3
3.0 m	1.02	1446.8
4.0 m	1.36	813.8
5.0 m	1.70	520.8
Ø (m)		E0(0°) [lx]

