

# Ontero IC

Article number: 21440005

## LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeColor |
| Luminous flux        | 1400 lm |
| System power         | 17 W    |
| Luminaire Efficiency | 82 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |
| Controller           | On/Off  |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 330°       |
| Swivel angle              | +/- 90°    |
| Weight                    | 1.1 kg     |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | black      |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, OvalBeam lens or honeycomb louve, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 330°, swivel angle +/- 90°, In-Track-Adapter, On/Off, 220-240 V~ / 50-60 Hz, temperature protection, max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

