

Ontero IC

Article number: 21459084

LIGHT TECHNOLOGY

LED	COB
Light colour	PearlWhite
Luminous flux	3720 lm
System power	41 W
Luminaire Efficiency	91 lm/W
Reflector	Medium
Beam angle	24°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Swivel angle	+/- 90°
Weight	1.1 kg
Protection rating . class	IP 20 . II
Luminaire colour	special colour


OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, OvalBeam lens or honeycomb louver, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, special colour, rotation angle 330°, swivel angle +/- 90°, On/Off, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.44	14717.0
2.0 m	0.88	3679.3
3.0 m	1.32	1635.2
4.0 m	1.76	919.8
5.0 m	2.20	588.7
Ø (m)		E0(0°) [lx]

