

## Ontero IC

Article number: 21460106

### LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 3850 lm    |
| System power         | 41 W       |
| Luminaire Efficiency | 94 lm/W    |
| Reflector            | Flood      |
| Beam angle           | 40°        |
| Controller           | On/Off     |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 330°       |
| Swivel angle              | +/- 90°    |
| Weight                    | 1.1 kg     |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | black      |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 330°, swivel angle +/- 90°, On/Off, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

