

## Ontero ID

Article number: 20610002

### LIGHT TECHNOLOGY

LED	COB
Light colour	835
Luminous flux	1420 lm
System power	17 W
Luminaire Efficiency	84 lm/W
Reflector	NarrowSpot
Beam angle	10°
Controller	On/Off

### LUMINAIRE

Rotation angle	330°
Swivel angle	90°
Weight	1.3 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 330°, swivel angle 90°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

