

## Ontero ID

Article number: 20620066

### LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeCool  |
| Luminous flux        | 2090 lm |
| System power         | 23 W    |
| Luminaire Efficiency | 91 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |
| Controller           | On/Off  |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 330°      |
| Swivel angle              | 90°       |
| Weight                    | 1.3 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 3 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, white, rotation angle 330°, swivel angle 90°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

