

## Ontero ID

Article number: 20620098

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | LED      |
| Light colour         | 835      |
| Luminous flux        | 4650 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 113 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 330°      |
| Swivel angle              | 90°       |
| Weight                    | 1.3 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |


### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, white, rotation angle 330°, swivel angle 90°, Multiadapter, Power-Adapter, Poti, 220-240 V~ / 50-60 Hz, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 28293.4     |
| 2.0 m | 0.68 | 7073.4      |
| 3.0 m | 1.02 | 3143.7      |
| 4.0 m | 1.36 | 1768.3      |
| 5.0 m | 1.70 | 1131.7      |
| Ø (m) |      | E0(0°) [lx] |

