

## Ontero SX

Article number: 21700005

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | BeNature |
| Luminous flux        | 530 lm   |
| System power         | 17 W     |
| Luminaire Efficiency | 31 lm/W  |
| Reflector            | Flood    |
| Beam angle           | 40°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 360°       |
| Swivel angle              | +/- 90°    |
| Weight                    | 0.58 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | black      |



Surface-mounted luminaire, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 95, chromaticity tolerance 2 SDCM (initial), miniaturized, vaporized plastic reflector, microfasetted, patented free-form optics (Bartenbach®) with clear and precise light distribution pattern, Reflector holder in plastic, black, high-gloss, reflector support ring with threaded connection and air inlet, die-cast aluminum, silver, housing and bracket in die-cast aluminium, powder-coated, Luminaire housing designed as a heat sink, black, Joint cover in housing color with decorative ring, edge area silver, matt (matt gold with Edition) rear perforated sheet metal cover for housing ventilation, rotation angle 360°, swivel angle +/- 90°, inclusive, On/Off, 220-240 V 50/60Hz, 400 mA, max. 36 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

