

Ontero XR

Article number: 20530040

LIGHT TECHNOLOGY


LED	COB
Light colour	BeColor
Luminous flux	2740 lm
System power	34 W
Luminaire Efficiency	81 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Swivel angle	+/- 85°
Weight	0.54 kg
Protection rating . class	IP 20 . II
Luminaire colour	white

OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head/retention arm die-cast aluminium, powder-coated, white, rotation angle 330°, swivel angle +/- 85°, In-Track-Adapter, On/Off, 220-240 V~ / 50-60 Hz, max. 27 luminaires per circuit (B16A fuse)

In-Track-Adapter 220-240 V~ / 50-60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.28	18088.8
2.0 m	0.56	4522.2
3.0 m	0.84	2009.9
4.0 m	1.12	1130.6
5.0 m	1.40	723.6
Ø (m)		E0(0°) [lx]

