

## Ontero XR

Article number: 20820004

### LIGHT TECHNOLOGY



|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | 927        |
| Luminous flux        | 1040 lm    |
| System power         | 17 W       |
| Luminaire Efficiency | 61 lm/W    |
| Reflector            | NarrowSpot |
| Beam angle           | 10°        |
| Controller           | On/Off     |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 400°      |
| Swivel angle              | +/- 85°   |
| Weight                    | 0.8 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 3 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 400°, swivel angle +/- 85°, Power-Adapter, DALI, 220-240 V~ / 50-60 Hz, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

