

Ontero XR

Article number: 20850022

LIGHT TECHNOLOGY


LED	COB
Light colour	PearlWhite
Luminous flux	1720 lm
System power	17 W
Luminaire Efficiency	101 lm/W
Reflector	Flood
Beam angle	44°
Controller	On/Off

LUMINAIRE

Rotation angle	400°
Swivel angle	+/- 85°
Weight	0.8 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, luminaire head/retention arm die-cast aluminium, powder-coated, silver, rotation angle 400°, swivel angle +/- 85°, Power-Adapter, DALI, 220-240 V~ / 50-60 Hz, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

