

## Ontero XR

Article number: 20910045

### LIGHT TECHNOLOGY



|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 4400 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 107 lm/W |
| Reflector            | Flood    |
| Beam angle           | 44°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 400°      |
| Swivel angle              | +/- 85°   |
| Weight                    | 0.8 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | silver    |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, luminaire head/retention arm die-cast aluminium, powder-coated, silver, rotation angle 400°, swivel angle +/- 85°, Power-Adapter, Poti, 220-240 V~ / 50-60 Hz, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

