

Ontero XR

Article number: 20770006

LIGHT TECHNOLOGY


LED	COB
Light colour	BeCool
Luminous flux	1400 lm
System power	17 W
Luminaire Efficiency	82 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

LUMINAIRE

Rotation angle	400°
Swivel angle	+/- 85°
Weight	0.8 kg
Protection rating . class	IP 20 . I
Luminaire colour	black


OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 400°, swivel angle +/- 85°, Power-Adapter, On/Off, 220-240 V~ / 50-60 Hz, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.34	8518.4
2.0 m	0.68	2129.6
3.0 m	1.02	946.5
4.0 m	1.36	532.4
5.0 m	1.70	340.7
Ø (m)		E0(0°) [lx]

