

## Ontero EC 125

Article number: 21010149

### LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 3480 lm    |
| System power         | 34 W       |
| Luminaire Efficiency | 102 lm/W   |
| Reflector            | OvalBasic  |
| Beam angle           | 60° x 40°  |
| Controller           | On/Off     |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 350°      |
| Swivel angle              | 210°      |
| Weight                    | 2.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, black, rotation angle 350°, swivel angle 210°, Multiadapter, On/Off, max. 34 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 5418.9 |
| 2.0 m | 2.10 0.82   | 1354.7 |
| 3.0 m | 3.15 1.22   | 602.1  |
| 4.0 m | 4.20 1.63   | 338.7  |
| 5.0 m | 5.25 2.04   | 216.8  |
| Ø (m) | E0(0°) [lx] |        |

