

Ontero EC 125

Article number: 21060106

LIGHT TECHNOLOGY

LED	COB
Light colour	Meat&Fish
Luminous flux	2670 lm
System power	41 W
Luminaire Efficiency	65 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

LUMINAIRE

Rotation angle	350°
Swivel angle	210°
Weight	2.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, silver, rotation angle 350°, swivel angle 210°, Multiadapter, On/Off, 220-240 V, 50/60 Hz, max. 24 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

