

Ontero EC 125

Article number: 21360017

LIGHT TECHNOLOGY


LED	COB
Light colour	830
Luminous flux	7460 lm
System power	59 W
Luminaire Efficiency	126 lm/W
Reflector	BatWing
Beam angle	2 x 35°
Controller	On/Off

LUMINAIRE

Rotation angle	350°
Swivel angle	210°
Weight	2.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver


OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with double asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing/head die-cast aluminium, silver, rotation angle 350°, swivel angle 210°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Distance (m)	Beam diameter (m)	Illuminance (lx)
1.0	3.46 3.10	563.0
2.0	6.92 6.20	141.0
3.0	10.38 9.30	63.0
4.0	13.84 12.40	36.0
5.0	17.30 15.50	23.0

