

Ontero EC 125

Article number: 21360022

LIGHT TECHNOLOGY


LED	COB
Light colour	835
Luminous flux	7740 lm
System power	59 W
Luminaire Efficiency	131 lm/W
Reflector	BatWing
Beam angle	2 x 35°
Controller	On/Off

LUMINAIRE

Rotation angle	350°
Swivel angle	210°
Weight	2.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	white


OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with double asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing/head die-cast aluminium, white, rotation angle 350°, swivel angle 210°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	3.46 3.10	575.0
2.0 m	6.92 6.20	144.0
3.0 m	10.38 9.30	64.0
4.0 m	13.84 12.40	36.0
5.0 m	17.30 15.50	23.0
Ø (m)	E0(0°)(lx)	

