

## Ontero XR

Article number: 20770097

### LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | 927     |
| Luminous flux        | 2860 lm |
| System power         | 34 W    |
| Luminaire Efficiency | 84 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |
| Controller           | On/Off  |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 400°      |
| Swivel angle              | +/- 85°   |
| Weight                    | 0.8 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | silver    |


### OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head/retention arm die-cast aluminium, powder-coated, silver, rotation angle 400°, swivel angle +/- 85°, Power-Adapter, On/Off, 220-240 V~ / 50-60 Hz, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 17402.0     |
| 2.0 m | 0.68 | 4350.5      |
| 3.0 m | 1.02 | 1933.6      |
| 4.0 m | 1.36 | 1087.6      |
| 5.0 m | 1.70 | 696.1       |
| Ø (m) |      | E0(0°) [lx] |

