

Pendiro EC 125

Article number: 81040071

LIGHT TECHNOLOGY



| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 2460 lm |
| System power | 23 W |
| Luminaire Efficiency | 107 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, white

Multidapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41 | 3830.6 |
| 2.0 m | 2.10 0.82 | 957.7 |
| 3.0 m | 3.15 1.22 | 425.6 |
| 4.0 m | 4.20 1.63 | 239.4 |
| 5.0 m | 5.25 2.04 | 153.2 |
| Ø (m) | E0(0°) [lx] | |

