

## Pendiro EC 125

Article number: 81010202

### LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 830       |
| Luminous flux        | 4970 lm   |
| System power         | 41 W      |
| Luminaire Efficiency | 121 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |
| Controller           | On/Off    |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.0 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 7739.1 |
| 2.0 m | 2.10 0.82   | 1934.8 |
| 3.0 m | 3.15 1.22   | 859.9  |
| 4.0 m | 4.20 1.63   | 483.7  |
| 5.0 m | 5.25 2.04   | 309.6  |
| Ø (m) | E0(0°) [lx] |        |

