

# Pendiro EC 125

Article number: 81000038

## LIGHT TECHNOLOGY

LED	COB
Light colour	830
Luminous flux	4230 lm
System power	34 W
Luminaire Efficiency	124 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

## LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

## OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.73	8399.1
2.0 m	1.46	2099.8
3.0 m	2.19	933.2
4.0 m	2.92	524.9
5.0 m	3.65	336.0
Ø (m)		E0(0°) [lx]

