

## Pendiro EC 125

Article number: 81000204

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 5150 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 126 lm/W |
| Reflector            | Flood    |
| Beam angle           | 40°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.0 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.77 | 10853.4     |
| 2.0 m | 1.54 | 2713.3      |
| 3.0 m | 2.31 | 1205.9      |
| 4.0 m | 3.08 | 678.3       |
| 5.0 m | 3.85 | 434.1       |
| Ø (m) |      | E0(0°) [lx] |

