

Pendiro EC 125

Article number: 81080314

LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 4060 lm    |
| System power         | 41 W       |
| Luminaire Efficiency | 99 lm/W    |
| Reflector            | Spot       |
| Beam angle           | 20°        |
| Controller           | On/Off     |

LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 2.7 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | white       |

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, white, separate driver unit

76500037 driver unit, On/Off, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.31 | 24519.9     |
| 2.0 m | 0.62 | 6130.0      |
| 3.0 m | 0.93 | 2724.4      |
| 4.0 m | 1.24 | 1532.5      |
| 5.0 m | 1.55 | 980.8       |
| Ø (m) |      | E0(0°) [lx] |

