

## Pendiro XR

Article number: 80770039

### LIGHT TECHNOLOGY



|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 2930 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 127 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 1.0 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 70 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 17827.9     |
| 2.0 m | 0.68 | 4457.0      |
| 3.0 m | 1.02 | 1980.9      |
| 4.0 m | 1.36 | 1114.2      |
| 5.0 m | 1.70 | 713.1       |
| Ø (m) |      | E0(0°) [lx] |

