

# Pendiro XR

Article number: 80730029

## LIGHT TECHNOLOGY

LED	COB
Light colour	BeColor
Luminous flux	1370 lm
System power	15 W
Luminaire Efficiency	91 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

## LUMINAIRE

Weight	1.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	white

## OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, white

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 104 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.34	8335.9
2.0 m	0.68	2084.0
3.0 m	1.02	926.2
4.0 m	1.36	521.0
5.0 m	1.70	333.4
Ø (m)		E0(0°) [lx]

