

Intara SX

Article number: 51640026

LIGHT TECHNOLOGY

| | |
|----------------------|---------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 1070 lm |
| System power | 17 W |
| Luminaire Efficiency | 71 lm/W |
| Reflector | Flood |
| Beam angle | 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|------------|
| Rotation angle | 220° |
| Swivel angle | +/- 20° |
| Weight | 0.45 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | white |



Recessed directional spot with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), vaporized plastic reflector, microfasetted, patented free-form optics with clear and precise light distribution pattern, heat sink die-cast aluminium, red anodized, mounting ring die-cast aluminum, white, powder-coated, rotation angle 220°, swivel angle +/- 20° clamp spring for ceiling attachment , including connected driver unit, On/Off, 220-240 V~ / 50-60 Hz, 400 mA, max. 60 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Inclusiv fix connected driver unit, On/Off 220-240 V~ / 50-60 Hz, max. 60 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

