

Intara SX


Article number: 51650016

LIGHT TECHNOLOGY

LED	COB
Light colour	927
Luminous flux	1130 lm
System power	15 W
Luminaire Efficiency	75 lm/W
Reflector	Downlight
Beam angle	60°
Controller	On/Off

LUMINAIRE

Rotation angle	0°
Swivel angle	0°
Weight	0.45 kg
Protection rating . class	IP 20 . II
Luminaire colour	black



Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), vaporized plastic reflector, microfasetted, patented free-form optics with clear and precise light distribution pattern reflector cover designed as a shadow gap, made of polycarbonate (PC), high-gloss black, heat sink die-cast aluminium, red anodized, mounting ring die-cast aluminum, black, powder-coated, rotation angle 0°, swivel angle 0° clamp spring for ceiling attachment , including connected driver unit, On/Off, 220-240 V~ / 50-60 Hz, 400 mA, max. 60 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Inclusiv fix connected driver unit, On/Off 220-240 V~ / 50-60 Hz, max. 60 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

