

## Intara XR

Article number: 50880027

## LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeColor |
| Luminous flux        | 1920 lm |
| System power         | 23 W    |
| Luminaire Efficiency | 83 lm/W |
| Reflector            | Medium  |
| Beam angle           | 24°     |
| Controller           | On/Off  |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Swivel angle              | +/- 25°    |
| Weight                    | 0.69 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | black      |

## OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, black,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.45 | 6655.0      |
| 2.0 m | 0.90 | 1663.8      |
| 3.0 m | 1.35 | 739.4       |
| 4.0 m | 1.80 | 415.9       |
| 5.0 m | 2.25 | 266.2       |
| Ø (m) |      | E0(0°) [lx] |

