

Intara XR

Article number: 50870013

LIGHT TECHNOLOGY


| | |
|----------------------|---------|
| LED | COB |
| Light colour | BeColor |
| Luminous flux | 1210 lm |
| System power | 15 W |
| Luminaire Efficiency | 81 lm/W |
| Reflector | Spot |
| Beam angle | 20° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|------------|
| Swivel angle | +/- 25° |
| Weight | 0.69 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | silver |

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, silver,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.34 | 7362.4 |
| 2.0 m | 0.68 | 1840.6 |
| 3.0 m | 1.02 | 818.0 |
| 4.0 m | 1.36 | 460.1 |
| 5.0 m | 1.70 | 294.5 |
| Ø (m) | | E0(0°) [lx] |

