

## Intara XR

Article number: 50770008

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 4360 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 106 lm/W |
| Reflector            | Flood    |
| Beam angle           | 44°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 400°       |
| Swivel angle              | +/- 85°    |
| Weight                    | 0.65 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | silver     |

### OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Semi-recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +/- 85°, silver, potentiometer to adjust the brightness, separate driver unit

76500109 driver unit, Poti, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

