

# Ontero TX


Article number: 21610032

## LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | SMD       |
| Light colour         | 835       |
| Luminous flux        | 5350 lm   |
| System power         | 38 W      |
| Luminaire Efficiency | 141 lm/W  |
| Reflector            | WideFlood |
| Beam angle           | 60°       |
| Controller           | On/Off    |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 300°       |
| Weight                    | 1.38 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | silver     |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern (60°), TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, silver, locking mechanism to aligned in 15° steps, rotation angle 300°, In-Track-Adapter, On/Off, 220-240 V~ / 50-60 Hz

In-Track-Adapter 220-240 V~ / 50-60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

