

# Ontero TX


Article number: 21610052

## LIGHT TECHNOLOGY

|                      |                             |
|----------------------|-----------------------------|
| LED                  | SMD                         |
| Light colour         | 830                         |
| Luminous flux        | 5420 lm                     |
| System power         | 38 W                        |
| Luminaire Efficiency | 143 lm/W                    |
| Reflector            | Doppelt Asymmetrisch Medium |
| Beam angle           | 2 x 25°                     |
| Controller           | On/Off                      |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 300°       |
| Weight                    | 1.38 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | white      |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, luminaire housing sheet steel, powder-coated, white, locking mechanism to aligned in 15° steps, rotation angle 300°, In-Track-Adapter, Casambi, On/Off, 220-240 V~ / 50-60 Hz

In-Track-Adapter On/Off, 220-240 V~ / 50-60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

