

## Ontero TX

Article number: 21600037

### LIGHT TECHNOLOGY

|                      |                |
|----------------------|----------------|
| LED                  | SMD            |
| Light colour         | 830            |
| Luminous flux        | 5190 lm        |
| System power         | 38 W           |
| Luminaire Efficiency | 137 lm/W       |
| Reflector            | Xtra WideFlood |
| Beam angle           | 90°            |
| Controller           | On/Off         |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 300°       |
| Weight                    | 1.16 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | black      |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, black, locking mechanism to aligned in 15° steps, rotation angle 300°, In-Track-Adapter, On/Off, 220-240 V~ / 50-60 Hz, max. 27 luminaires per circuit (B16A fuse)

In-Track-Adapter 220-240 V~ / 50-60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

