

## Ontero TX

Article number: 21410005

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | SMD       |
| Light colour         | 835       |
| Luminous flux        | 10630 lm  |
| System power         | 72 W      |
| Luminaire Efficiency | 148 lm/W  |
| Reflector            | WideFlood |
| Beam angle           | 60°       |
| Controller           | On/Off    |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 330°      |
| Weight                    | 3.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern (60°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6010 lm), 42 W (6700 lm), 47 W (7380 lm), 52 W (8050 lm), 57 W (8710 lm), 62 W (9360 lm), 67 W (10000 lm), 72 W (10630 lm), 57 Watt preselected, rotation angle 330°, DALI OT, DIP-Switch, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 21 luminaires per circuit (B16A fuse)

inclusiv driver unit: 220-240 V~ / 50-60 Hz, DALI, max. 15 luminaires per circuit (B16A fuse), temperature protection, temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

