

# Ontero TX


Article number: 21420005

## LIGHT TECHNOLOGY

LED	SMD
Light colour	835
Luminous flux	10520 lm
System power	72 W
Luminaire Efficiency	146 lm/W
Reflector	Xtra WideFlood
Beam angle	90°
Controller	On/Off

## LUMINAIRE

Rotation angle	330°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	white



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (5940 lm), 42 W (6630 lm), 47 W (7300 lm), 52 W (7960 lm), 57 W (8610 lm), 62 W (9250 lm), 67 W (9890 lm), 72 W (10520 lm), 57 W preselected, rotation angle 330°, DALI OT, DIP-Switch, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 21 luminaires per circuit (B16A fuse)

inclusiv driver unit: 220-240 V~ / 50-60 Hz, DALI, max. 15 luminaires per circuit (B16A fuse), temperature protection, temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

