

Ontero TX


Article number: 21620001

LIGHT TECHNOLOGY

LED	SMD
Light colour	830
Luminous flux	10760 lm
System power	72 W
Luminaire Efficiency	149 lm/W
Reflector	Doppelt Asymmetrisch Medium
Beam angle	2 x 25°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	black



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6090 lm), 42 W (6780 lm), 47 W (7470 lm), 52 W (8450 lm), 57 W (8810 lm), 62W (9470 lm), 67 W (10120 lm), 72 W (10760 lm), 57 Watt preselected, rotation angle 330°,luminaire housing sheet steel, powder-coated, black, Multiadapter

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

