

Pendiro TX

Article number: 80890001

LIGHT TECHNOLOGY

LED	SMD
Light colour	830
Luminous flux	9140 lm
System power	64 W
Luminaire Efficiency	143 lm/W
Reflector	MediumFlood
Beam angle	30°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Weight	3.7 kg
Protection rating . class	IP 20 . III
Luminaire colour	matt black



Suspended luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern 30°, TIR-lens made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (5770 lm), 38 W (5830 lm), 42 W (6320 lm), 45 W (6800 lm), 49 W (7280 lm), 53 W (7750 lm), 56 W (8220 lm), 60 W (8680 lm), 64 W (9140 lm), 53 W preselected, luminaire housing sheet steel, powder-coated, matt black, power supply via suspension cables.



Canopy, sheet steel, powder-coated, including SELV driver with adjustable system performance via DIP switch, temperature protection, canopy /supply set (E-set) please order separately:

76500078 E-Set for 3-Ph Track, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), black matt, DIP-Switch 38W-64W (default 53W), temperature protection, matt black

76500079 E-Set with Canopy, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), black matt

76500082 E-Set for 3-Ph Track, DALI, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), black matt

76500083 E-Set with Canopy, DALI, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), black matt



Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

